

ARGOX CAN.

Outstanding Series Barcode Printer (OS-214 plus)



OS-214 plus

OS-214 plus

The OS-214 plus is the newest generation of Argox's most successful medium volume printer model. Its attractive and stylish design is just one of several new features and advanced functions. The significantly larger onboard memory increases print capability for producing a wider range of label applications. A full-speed USB 2.0 interface adds flexibility for use with any of today's notebook and other computers. Its space-saving design offers the same small footprint and light weight as previous models for easy and convenient placement. The new OS-214 plus maintains Argox's leading position as the industry standard for style, price, and performance.



Model name	OS-214 PLUS
Printing method	Direct Thermal / Thermal Transfer
Printing resolution	203 dpi (8 dots/mm)
Printing speed	2 ~ 3 ips (51 ~76 mm/s)
Printing length	43" (1092 mm)
Printing width	Max 4.1" (104 mm)
Memory	8MB DRAM 4MB Flash ROM
CPU type	32 bit RISC microprocessor
Media sensor	Reflective
Display	LED indicators x 2
Operation interface	Button x 1
Communication interface	Centronics parallel RS-232 serial USB
Barcodes	Code39、Extended Code39、Code93、Code128 UCC、Code128 subset A/B/C、Codabar、Interleave 2 of 5、EAN-8 2&5 add on、EAN-13、EAN-128、UPC、UPC-A, E 2&5 add on、POSTNET、German POST、Matrix 25、Maxicode、PDF-417、Data Matrix
Fonts	Int'l character sets standard 5 alpha-numeric fonts from .049"~ .23"H (1.25mm ~ 6.0mm) All fonts are expandable up to 24x 24 4 direction 0°~270° rotation Soft fonts are downloadable
Graphic	PPLA: PCX, BMP, IMG, HEX, GDI PPLB: PCX, Binary raster, GDI
Software	Argox PPLA and PPLB Window Driver (Win 98/2000/NT/XP) Label editing software - ArgoBar Pro / Print Utility / Bartender
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper Max width 4.25" (108 mm) Min width 1" (25.4 mm) Thickness .0025"~. 01" (.0635mm ~. 254mm) Max roll capacity 4.3" (109 mm) OD Core size 1" (25mm) ID
Ribbon	Wax, Wax/Resin, Resin Ribbon width - 2"~ 4" Ribbon roll - max OD 1.45" (37 mm) Ribbon length - max 91 m Core size - ID .5" core (13 mm) with notch
Dimensions	W186 mm x L278 mm x H153 mm
Weight	4.2 lbs (1.9kgs)
Power source	EDAC universal switching power supply Input: 100V~240V, 1.8A, 50~60Hz Output: 24VDC, 2.1A, 50W Max.
Safety approval	CE, UL, CUL, FCC class A, CCC
Operation environment	Operation temperature: 4°C~38°C 10~90% non condensing Storage temperature: -20°C~50°C
Optional items	Cutter, Dispenser kit, Real Time clock card, 2MB Asian Font card (Traditional Chinese, Simplified Chinese, Korean and Japanese), ArgoKee

Specifications subject to change without notice

